



Firmly in control.





- Intuitive operation of all controls
- Forward/reverse drive, lift, lower and fork tilt controlled by multi-function lever
- All functions conveniently controlled by one hand
- Control lever doubles as hand grip





Operators compartment



- Excellent working posture, best visibility in both directions
- Low access step, only 95 mm high
- Hydraulically adjustable driver's platform





Tops in handling.



- Tapered, rounded chassis
- Extremely maneuverable
- Suitable for operation in tightest spaces
- Safety for load carried







Features



- Load capacity: 1.000 kg at 600 mm load centre up to 5.255 mm lift height
- Universal truck for both indoor and outdoor applications







Power plant.

- Adequately sized 2.2 kW traction motor
- Safely housed inside counterweight







Performance boost.



- Digital microprocessor control, 16 kHz high-frequency system
- Energy-economizing, quiet, accurate
- Booster effect on startup (two-second starting current increase)
- Automatic electronic deceleration





Axle

• Load wheels with string ingress protection







Safety in every situation.

Three independent braking systems:

- Countercurrent braking
- Regenerative braking with multi-function control lever at neutral
- Hydraulic drum brake on load wheels, operated by brake pedal







Security first



Added safety

Parking brake applied automatically when operator dismounts







E 10 easy steering.



- Compact ergonomic-design steering wheel
- Hydrostatic power steering, small resistance
- Sensitive, precise operation
- Steering lock 92 degrees left and right





Comfort for the operator.



- Hydraulic adjustment of platform height
- Padded backrest at side for comfortable support
- Overhead guard optimized for visibility
- Small steering effort due to large steering wheel and power assist
- Emergency cut-out in close reach
- Beverage holder







Productivity from ergonomy



Excellent ergonomical features mean fatigue-free working - the operator can maintain a high level of concentration for a longer period.





Example I



Freight truck loading/unloading at ground level





Example III



Production shop duty







Stacking I







Stacking II







Stacking







Distance hauling







Standard Equipment

- Fork length: 1150 mm
- Precise, energy saving Linde Digital Control
- Twist grip facilitating traction and all mast functions
- Hydraulically adjustable rider platform
- Combined hour meter and battery discharge indicator with lift cut-out

